

SAFE-T-GUARD

ROOF WALKWAY MATS

Rooftop Safety

National Rubber Technologies Corp.'s Symar Safe-T-Guard mats have been engineered with raised buttons on the surface, ensuring positive traction in all weather conditions. Water is channeled below the safety surface reducing the chances of slips and trips.



Easy Installation

Safe-T-Guard Roof Walkway Mats are manufactured using Symar masticated rubber which can be firmly adhered with compatible commercial roofing adhesives. For even easier installation, Safe-T-Guard Mats are available with a specialized PSA tape for simple peel and stick installation.

SPECIFICATIONS		TOLERANCE
Thickness:	5/16"	+/- 0.020"
Width:	30"	+/- 0.250"
Length:	30"	+/- 0.250"
Weight:	8 lb.	
Standard Pack Size:	50 mats./skid	



Durability and Protection

Safe-T-Guard's durable Symar rubber compound ensures maximum protection for valuable EPDM and **PVC** roofing membranes. Safe-T-Guard Roof Walkway Mats eliminate surface wear on membranes in high traffic areas, while greatly reducing the chance of membrane punctures. Year after year, Safe-T-Guard Roof Walkway Mats stand up to all weather conditions.

National Rubber Technologies makes no representations or warranties with respect to the suitability of materials for a particular purpose. Buyers and users must determine the safety and suitability of National Rubber Technologies' products for their own purposes and assume all risk, responsibility, and liability for all injuries, losses, or damages arising from the application of the information or use of National Rubber Technologies' products, whether or not occasioned by National Rubber Technologies' negligence or based on strict product liability.

CUSTOMER SERVICE: 1-800-387-8501 info@nrtna.com

A KN RUBBER COMPANY

